MI404 PRO/MI406 PRO/MI413 PRO/MI414 PRO

Free & Total Chlorine and Chloride Photometers

Milwaukee provides a range of chlorine photometers for all applications: swimming pool treatments, household cleaners, dishwasher additives, laundry powders/ liquids and cooling water treatment products all contain chlorine as an oxidizing biocide. Drinking water contains residual chlorine to maintain water purity throughout the supply lines.

Milwaukee offers microprocessor-based instruments with greater resolution, better accuracy and immediate results.

You can choose between three different models: MI404 PRO for measuring free (0.00 to 5.00 mg/L) and total (0.00 to 5.00 mg/L) chlorine, MI406 PRO for measuring free (0.00 to 5.00 mg/L) chlorine and MI413 PRO for measuring free (0.00 to 10.00 mg/L) and total (0.00 to 10.00 mg/L) chlorine.





Chloride is a major constituent of sea water and is extremely corrosive in acidic environments. It requires close monitoring in applications such as marine boiler systems that are effected by seawater contamination.

Chlorides are used by the water treatment professional to determine cycles of concentration in low pressure boilers and cooling systems.

It is essential to monitor chloride concentrations in boiler systems to prevent metal parts being damaged. In high levels, chloride can corrode stainless steel.

Milwaukee offers the MI414 PRO microprocessor-based photometer for measuring chloride (0.00 to 20.00 mg/L).

Specificati	ions	MI404 PRO	MI406 PRO	MI413 PRO	MI414 PRO
		Free & Total Chlorine	Free Chlorine	Free & Total Chlorine HR	Chloride
	ee Chlorine tal Chlorine	0.00 to 5.00 mg/L (Cl ₂) 0.00 to 5.00 mg/L (Cl ₂)	0.00 to 5.00 mg/L (Cl ₂)	0.00 to 10.00 mg/L (Cl ₂) 0.00 to 10.00 mg/L (Cl ₂)	
	Chloride ee Chlorine tal Chlorine	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L) 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.00 to 20.00 mg/L (Cl')
Accuracy Fre	Chloride ee Chlorine	±0.06 mg/L @1.50 mg/L	±0.06 mg/L @1.50 mg/L	±0.17 mg/L @1.50 mg/L	0.01 mg/L
	tal Chlorine Chloride	±0.06 mg/L @1.50 mg/L		±0.17 mg/L @1.50 mg/L	±1.0 mg/L @10.0 mg/L
Method		adaptation of USEPA method 330.5 and Standard Method 4500-CI G	adaptation of USEPA method 330.5 and Standard Method 4500-CI G	adaptation of USEPA method 330.5 and Standard Method 4500-CI G	adaptation of mercury (II) thiocyanate method
Light Source Light Detector		tungsten lamp silicon photocell and 525 nm narrow band interference filter	tungsten lamp silicon photocell and 525 nm narrow band interference filter	tungsten lamp silicon photocell and 525 nm narrow band interference filter	Blue LED 466 nm silicon photocell and 466 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%
Battery Type		1 x 9 V	1 x 9 V	1 x 9 V	1 x 9 V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Packaging dimensions Packaging weight		305 x 280 x 115 mm 1.24 kg	305 x 280 x 115 mm 1.26 kg	305 x 280 x 115 mm 1.52 kg	305 x 280 x 115 mm 1.44 kg

Accessories

Mi504-100 Free & Total Chlorine liquid reagent set (100 tests)

Mi506-100 Free Chlorine liquid reagent set (100 tests)

Mi513-045 Free & Total Chlorine liquid reagent set (45 tests)

Mi514-100 Chloride liquid reagent set (100 tests)



(100 tests) Mi526-100 Free Chlorine powder reagents

(100 tests)


Glass cuvets (2 pcs)

Caps for cuvets (2 pcs)

Stoppers for cuvets (2 pcs)















MI404 PRO, MI406 PRO, MI413 PRO and MI414 PRO are supplied complete with 2 cuvets, reagents, hard carrying case, wiping tissue, 9V battery and instructions.

DISTRIBUTOR: - BLUE HORIZON

Gopal Niwas, 135, Princess Street Mumbai-400002 INDIA Tel: +91 9820206611 Email: sales.bluehorizon@gmail.com

Mi0002

Mi0003



